

GPPS 1160 Technical Datasheet

Product Description:

GPPS1160 is a high heat resistance and molecular weight crystal polystyrene for extrusion and bi oriented polystyrene(OPS) industry. It is particularly useful in the production of thick sheet by direct inject gassing, where it gives expanded sheets with high mechanical properties GPPS1160 can also be used in dilution with HIPS7240 for extrusion of sheet for thermoforming. This grade has food contact approval.

Features:

PROPERTY	UNIT	TEST METHOD	TYPICAL VALUE
MELT FLOW INDEX(200□C-5KG)	g/10min	ASTM D-1238	2.5
STYRENE RESIDUAL MONOMER	PPM	CLG LABPSG004 (ATOFINA TEST METHOD)	<500
VICAT SOFTENING POINT (50 °C/hr 1kg)	°C	ASTM D-1525	105
ROCKWELL HARDNESS	-	ASTM D-785	SCALE/L70
TENSILE STRESS AT BREAK	MPA	ASTM D-638	48
ELONGATION AT BREAK	%	ASTM D-638	3
TENSILE MODULUS	MPA	ASTM D-638	3200


Applications:

shower cabinets, lighting thin films, insulation board, foam sheet of fruits trays, meat trays, egg boxes.



 Unit 302, Sheydayee BLD, Sazman AB, Tehranpars

 <https://irplastics.com/en>

 +98-21-77784838

