

Manufacturer			Product Name	
MTA Holding			Light Hydrocarbon (N) [B]	
R	Property	Unit	Test Method	Limit
1	Density @ 15°C	g/cm ³	ASTM D1298	0.700-0.730
2	Total Sulfur	ppm	ASTM D4294	1000 max
3	Color	*	ASTM D156	+20 min
4	Copper corrosion (3hr@50°C)	*	ASTM D130	1a
5	Aromatic	Vol%	ASTM D5580	20 max
	Total Paraffin			50 min
6	I.B.P	°C	ASTM D86	40 min
	FBP			180-190

Manufacturer			Product Name	
MTA Holding			Light Hydrocarbon (N) [C]	
R	Property	Unit	Test Method	Limit
1	Density @ 15°C	g/cm ³	ASTM D1298	0.730 min
2	Total Sulfur	ppm	ASTM D4294	1000 max
3	Color	*	ASTM D156	+20 min
4	Copper corrosion (3hr@50°C)	*	ASTM D130	1a
5	Aromatic & Naphthene	Vol%	ASTM D1319	35 min
	Total Paraffin		ASTM D5580	50 min
6	I.B.P	°C	ASTM D86	55 min
	FBP			185-195

Manufacturer			Product Name	
MTA Holding			Light Hydrocarbon (N) [C]	
R	Property	Unit	Test Method	Limit
1	Density @ 15°C	g/cm3	ASTM D1298	0.730 min
2	Total Sulfur	ppm	ASTM D4294	1000 max
3	Color	*	ASTM D156	+20 min
4	Copper corrosion (3hr@50°C)	*	ASTM D130	1a
5	Aromatic & Naphthene	Vol%	ASTM D1319	35 min
	Total Paraffin		ASTM D5580	50 min
6	I.B.P	°C	ASTM D86	55 min
	FBP			185-195